



TECHNICAL DATA SHEET #51

F-848 eccs®

Water Base Vinyl Urethane Net/ Fabric Coating FOR INDUSTRIAL USE ONLY

DESCRIPTION:

F-848 eccs water base vinyl urethane coating is specifically developed to seal and protect fishing and athletic netting as well as seal and protect rope and other natural and synthetic materials. F-848 is very economical and non-flammable. F-848 is available as a dipping formulation only.

SPECIFICATIONS:

Solids: (wt.) 36%

Shelf life: 1+ years at 77°F unopened container

Finish: matte

Chemical resistance:

Petroluems, alchols, moisture, urine, acids- excellent

Aromatics, aliphatics- good

Ketones- limited

SURFACE PREPARATIONS:

MIX WELL BEFORE USE.

All surfaces to be coated must be free of any oils, dust, release agent build up or loose fiber particles.

USE ADEQUATE VENTILATION.

DIPPING: GENTLY MIX BEFORE DIPPING.

Emmerse netting into F-848 and allow to soak for 2-4 minutes minimum[maybe longer depending on weave and overall thickness]. Remove netting from F-848 and lightly shake excess coating from net and allow to run back into dipping container to minimize waste.

If air drying allow 24 hours drying before packaging. To speed drying process, allow F-848 to set up at room temperature for 10-15 minutes then use mild [115-150 f] heat and air movement for 4-6 hours or until completely dry before packaging.

Contact OEM Technical Support for more details regarding your specfic application and process.

We cannot anticipate all conditions under which this information and our products, or the products of other manufacturers in combination with our products, may be used. We accept no responsibility for results obtained by the applications of this information or the safety and suitability of our products, either alone or in combination with other product combination for their own purposes. Unless otherwise agreed in writing, we sell the products without warranty, and buyers and users assume all responsibility and liability for loss or damage arising from the handling and use of our products whether used alone or in combination with other products. Ever changing V.O.C. regulations in your area may require you to contact local authorities for proper use and/or disposal of this product. Should you need further assistance, please contact PLASTI DIP INTERNATIONAL technical service.

Eccs is a registered trademark of PLASTI DIP INTERNATIONAL
Performix and logo are trademarks of PLASTI DIP INTERNATIONAL

REVISED 6/05/07
PDC F-848